

INCONTRI ELETTRICI IN ACCIAIO INOX PER SERRATURE CASSA 15 MM CON CATENACCIO AVANZANTE (1600S - 1700S) O CON CATENACCIO BASCULANTE (1400S - 1500S)
STAINLESS STEEL ELECTRIC STRIKING PLATES FOR LOCKS WITH 15 MM LOCKCASE AND ADVANCING BOLT (1600S - 1700S) OR TIPPING BOLT (1400S - 1500S)



		Sganciamento permanente <i>Hold-open</i> 9-16 V a.c./d.c.	Sganciamento momentaneo <i>Fail-secure</i> 9-16 V a.c./d.c.	Antipanico <i>Fail-safe</i> 12 V d.c.	Adatta a profili tipo <i>Suitable for profiles</i>
Con frontale piano <i>Flat faceplate</i>		cod. 02546XEL60	cod. 02546XEL61	cod. 02546XEL72	Profili piani <i>Flat profiles</i>
Con frontale regolabile <i>Adjustable faceplate</i>		cod. 02346XEL60	cod. 02346XEL61	cod. 02346XEL72	C.E. Finestra <i>Euro Groove Windows</i>
		cod. 02646XEL60	cod. 02646XEL61	cod. 02646XEL72	C.E. Porta <i>Euro Groove Doors</i>
		cod. 02846XEL60	cod. 02846XEL61	cod. 02846XEL72	R40 - R50
		cod. 03046XEL60	cod. 03046XEL61	cod. 03046XEL72	All.co P4 Sormonto

INCONTRI ELETTRICI IN ACCIAIO INOX PER SERRATURE CASSA 19 MM CON CATENACCIO BASCULANTE (1400 - 1500)
STAINLESS STEEL ELECTRIC STRIKING PLATES FOR LOCKS WITH 19 MM LOCKCASE AND TIPPING BOLT (1400 - 1500)



		Sganciamento permanente <i>Hold-open</i> 9-16 V a.c./d.c.	Sganciamento momentaneo <i>Fail-secure</i> 9-16 V a.c./d.c.	Antipanico <i>Fail-safe</i> 12 V d.c.	Adatta a profili tipo <i>Suitable for profiles</i>
Con frontale piano <i>Flat faceplate</i>		cod. 02526XEL60	cod. 02526XEL61	cod. 02526XEL72	Profili piani <i>Flat profiles</i>
Con frontale regolabile <i>Adjustable faceplate</i>		cod. 02396XEL60	cod. 02396XEL61	cod. 02396XEL72	C.E. Finestra <i>Euro Groove Windows</i>
		cod. 02696XEL60	cod. 02696XEL61	cod. 02696XEL72	C.E. Porta <i>Euro Groove Doors</i>
		cod. 02896XEL60	cod. 02896XEL61	cod. 02896XEL72	R40 - R50
		cod. 03096XEL60	cod. 03096XEL61	cod. 03096XEL72	All.co P4 Sormonto